



FITTING INSTRUCTIONS:

Before fitting the respirator, *carefully inspect the entire respirator* to ensure that the respirator is not damaged and is functioning correctly. *Discard the entire respirator if any part does not function properly.*

1. Hold the respirator in your hand with the nosepiece at your fingertips and allowing the straps to fall below the hand.
2. Place respirator under the chin with the nosepiece (narrow end) up. Raise the continuous top strap over your head and place it high to the back of the head.
3. Pull the continuous bottom strap over your head and position it around the neck below the ears.
4. Using both hands, push the nosepiece inwards with your fingertips to mold and shape the nose area to the face.
5. A seal check **MUST** be performed each time the user enters a contaminated area. Lightly cup both hands over the front of the respirator and **INHALE SHARPLY**. A negative pressure should be felt inside of the respirator. If any air flow is detected around the edges of the respirator, readjust the straps. Repeat seal check until a proper seal is achieved; otherwise, see your supervisor. ***NEVER enter a contaminated area without a proper seal.***

Note: Pinching the nosepiece using one hand may result in improper fit and less effective respirator performance. Use two hands.

Special Instructions: The model F720 filtering facepiece respirator has been manufactured by Approval Holder Fido Masks CO., Ltd. for SBM International Trading FZCO (Brand Name: Vaultex) under TC-84A-7792.

Lot No. XXXXXX

(the Lot No. XXXXXX will be as same as abbreviated Label indicated, the "XXXXXX" should be printed as purchase order number)

Contents: 20 pcs.